CP-DY60L2-E



High Resolution IR Dome Camera - 20 mtr





- \Rightarrow 1/3" Sony Super HAD II
- \Rightarrow 600 TVL High Resolution Camera
- \Rightarrow 0 lux @ F1.2 (IR ON)
- \Rightarrow 3.6 mm Fixed Lens
- \Rightarrow IR Range of 20 Mtrs with 24 LED's
- \Rightarrow AGC, AWB and BLC
- \Rightarrow Sens Up
- $\Rightarrow\,$ CE, FCC and RoHS Certified











Feature

Image Sensor

Certifications







1/3" Sony Super HAD II

Specification

CE, FCC, RoHs

| inage sensor | 1/3 Sony Super FIAD II |
|-------------------------|-------------------------------|
| Pixels | PAL:752Hx582V, NTSC:768Hx494V |
| Resolution | 600 TVL |
| Min. Illumination | 0 lux @F1.2 |
| S/N Ratio | more than 48dB |
| Electronic Shutter | 1/50(1/60) - 1/100000 Sec |
| Lens | 3.6 mm |
| Gamma Correction | 0.45 |
| White Balance (AWB) | Auto |
| Gain Control (AGC) | Auto |
| Back Light Compensation | ON/OFF Selectable |
| IR | 24 LEDs, Upto 20 Mtrs |
| Sync | Internal/External Line Lock |
| Video Output | 1.0 Vp-p/75 ohm |
| Special Functions | Sens-Up(Low Shutter)=x512 |
| Power Supply | DC 12V ± 5% |
| Power Consumption | <5W |
| Dimensions | 140 x 96 |
| Weight | 1100 |
| Operating Temperature | -20~50 °C |